

Technical Specification

TT-select[®] S850 HDTV

Digital receiver for HDTV and DVB-S2



Based on TT-select[®] family

BASICS

- DVB satellite receiver compliant to EN 302 307
- MPEG-2 and MPEG-4 AVC/H.264 video decoding
- HDMI output
- 16 digit dot-matrix front display
- Video support for 574p, 720p and 1080i
- Internal power supply incl. switch
- Video and Audio out via SCART
- Digital Audio out via optical S/PDIF
- Analogue Audio out (left/right) via RCA (Cinch)
- MPEG -2 compliant: ISO/IEC 13818-1
- Video Decoding:
 - ISO/IEC 13818-2 (MPEG-2 Video)- MP@ML & MP@HL
 - ISO/IEC 14496-10 (MPEG-4/Part 10) – HP@4L
 - High Definition and Standard Definition: 1080i50, 720p50, 576i25
- Audio Decoding:
 - ISO/IEC 13818-3 (MPEG-1/2, Layer 1, 2 & 3)
 - ISO/IEC 14496-3 (MPEG-4/AAC-HE)
 - Dolby AC-3 pass-through and down-mix
- Automatic FEC selection: 1/2, 2/3, 3/4, 5/6, 7/8
- Common Interface slot
- Update over the satellite network and USB

POWER SUPPLY

- Power supply 230 VAC/50Hz to 12VDC
- Power consumption in operation mode less than 20 W
- Power consumption in standby less than 1 W
- On/Off switch

ACCESSORIES

- Receiver (ca. 432 x 250 x 57 [mm])
- Euro-SCART cable
- Remote Control including battery
- Instruction manual: A5 format black/white
- Standard HDMI[®] Cable

LNB control

- Band selection: 22 KHz
- Polarity selection: 14/18 V
- Tone burst mode
- DiSEqC 1.0
- LNB support maximal 400 mA

HIGHLIGHTS

- Reception of High Definition
- HDMI interface
- Inclusive up-to-date perfect upscale technology

FRONT PANEL



BACK PANEL



REMOTE CONTROL



AWARDS



TechnoTrend Görler GmbH, Ing.-Anton-Kathrein-Strasse 2, 83101 Rohrdorf-Thansau
Phone: +49 (0) 89 255515-221, Fax: +49 (0) 89 255515-229, www.ttgoerler.com

All rights reserved. Subject to changes in technology, design and availability. The product names mentioned in this document are trademarks or registered trademarks of their respective owners.

Version October 2010

Technical Specification

TT-select[®] S850 HDTV

Digital receiver for HDTV and DVB-S2



Based on TT-select[®] family

STB MODE FUNCTIONALITY

- DVB satellite TV and Radio reception
- 16 digit dot-matrix front display
- Pay- and Free-TV support
- Reception of High Definition and Standard Definition
- Excellent Easy-To-Use graphical user interface
- Context referred help function
- Automatic and manual channel scan
- Separated program list for TV and Radio
- Up to 4 different favourite lists
- Up to 4000 programs storable
- Electronic Program Guide (EPG): present/following program plus additional 7-days EPG
- Automatic format shift form 4:3 and 16:9
- One-Touch Timer setting in EPG
- Simultaneous display of HD content on HDMI and SD content on SCART
- Multi language support, e.g. German, English, Swedish and Finnish
- Integrated Tele text browser and Tele text re-insertion (VBI)
- DVB and EBU subtitling support (ETS 300 743)

RF SPECIFICATION

- QPSK demodulation compliant to DVB satellite standard EN 302 307
- Frequency range: 950...2150 MHz
- Symbol rate: 1...45 Msymbole/s (SCPC & MCPC)
- INPUT RF level: -25...-65 dBm
- Input connector: IEC F-type female
- Input termination 75Ω

For DVB-S

- SCPC/MCPC support 2 Msymbol/s to 45 Msymbol/s
- QPSK with supported rates 1/2, 2/3, 3/4, 5/6, 6/7, 7/8
- Viterbi soft decoder rate 1/2
- Support of Reed-Solomon decoding (EN 300 421)
- Up to 60 Mbps channel bit rate

For DVB-S2

- Broadcast profile
- SCPC/MCPC support 10 Msymbols/s to 30 Msymbol/s
- QPSK and 8PSK with supported rates 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
- LDPC and BCH decoder as per DVB-S2 requirements
- Digital Nyquist root filter with 0.20, 0.25, 0.35 roll-off factors
- Up to 90 Mbps channel bit rate

STANDARD + REGULATION COMPLIANCE

- DVB satellite standard EN 302 307
- MPEG-2 Transport Stream support to ISO/IEC 13818-2
- MPEG-4/Part 10 Transport to ISO/IEC 14496-10
- MPEG-1/2, Layer 1,2 & 3 – Audio support compliant to ISO/IEC 13818-3
- MPEG-4 Audio support compliant to ISO/IEC 14496-3
- Tele text in VBI according to ETS 300 472
- Safety and EMC regulations: EN 55013, EN 55020 and EN 60065

INPUT / OUTPUT SPECIFICATION

- 2x Input connector: female IEC F-Type (75Ω)
- Digital HDMI Video out
- 2x SCART out (TV & VCR) accordingly to EN 50049-1
- TV SCART out: CVBS, Y/C, RGB, Audio
- VCR SCART out: CVBS, Y/C, Audio
- VCR SCART in (pass to TV SCART): CVBS, Y/C, Audio
- Switching signal: at PIN 16 0/1-3 V
- RCA out (Cinch)
- 3x Component Video out – YpbPr
- 2x Analogue Audio out (left/right)
- 1x Digital Audio out
- Digital Audio out (PCM stereo, AC3) via optical S/PDIF
- Common Interface
- USB 2.0 connector

LOGOS



EAN

- 42 6006463 366 8



TechnoTrend Görler GmbH, Ing.-Anton-Kathrein-Strasse 2, 83101 Rohrdorf-Thansau
Phone: +49 (0) 89 255515-221, Fax: +49 (0) 89 255515-229, www.ttgoerler.com

All rights reserved. Subject to changes in technology, design and availability. The product names mentioned in this document are trademarks or registered trademarks of their respective owners.

Version October 2010